

DURA-POST[®] STRAIGHT EDGE STEEL GUIDE & MARKER POSTS

Product Codes: FSG SERIES

DIMENSIONS AND SPECIFICATIONS

WIDTH	102mm (+ or - 2mm wide) with a flat surface width of 51mm both front and rear.
LENGTH	1350mm, 1500mm, 1650mm
DEPTH	Minimum 350mm
EXPOSED LENGTH ABOVE GROUND (RECOMMENDED)	1000mm (VIC 1050mm)
SHAPE	Straight edge with recess to protect delineation

DESCRIPTION

Classified as a Rigid Road Edge Guidepost, the post is made from high tensile galvanised steel pointed at the bottom for ease of manually or mechanically installing. The depth mark hole and sticker denote the depth mark and product identification with date of manufacture. The removal hole simplifies the installation and removal process with the manual driver and removal tool.

DURABILITY

The guideposts will not support combustion however are fire resistant and powder coating can withstand temperatures of up to 140°C. The post has capabilities of retaining a minimum of 85% of their colour, appearance and physical properties when exposed to extreme conditions for at least 8 years.

COLOUR AND FINISH

The guidepost is manufactured from galvanised steel and coated with Dulux[®] powder coat to approx. 80-micron film thickness in a standard white or colour for marker posts.

PHYSICAL PROPERTIES

NATA test reports have been completed on the guidepost and are available upon request. When installed in correct vertical position will not deflect when subjected to wind speeds of 33m/sec. The post

can be restraightened up to 20 times.

COMPLIANCE

The Dura-Post rigid steel guidepost passes the Australian Standard AS1742.2-2009 and individual state compliances, including Department of Main Roads QLD MRTS14 December 2013 clauses 10.2.2 to 10.2.2.6 and product type description "Rigid REGPs: posts either incapable of returning to their original state post impact or requiring assistance by hand or mechanical means to return to, or within a margin of 5 degrees, of their original state."

DELINEATION

Delineation can be fitted to front and rear of post for visibility to suit state and national specifications Class 1A 10,000mm² (50 x 200mm).

END CAPS

Safety end caps are supplied on request. They are manufactured from UV stabilised high density polyethylene to prolong life of post.

PACKAGING

Posts are packaged in boxes of ten (24kg in total) and palletised to suit.

WARRANTY

Roadside Products offers a 10 year manufacturer's limited warranty for the Steel Guide Post System.

TERMS

This information and our technical advice, whether verbal, in writing or by way of trials, are given in good faith but without warranty. This also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided, especially that contained in our safety data and technical information sheets, and to test our products as to their suitability for the intended processes and uses.

The application use and processing of our products and the products used by you based on our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our general conditions of sale and delivery.